

## YSHIELD® GK5 | Primer concentrate | 1 liter

High quality primer supplied as concentrate, makes 5 liters of primer. TÜV-SÜD certified.

---



YSHIELD® GK5

YSHIELD GmbH & Co. KG  
Rotthofer Straße 1  
94099 Ruhstorf, Germany  
Further information:  
[www.yshield.com](http://www.yshield.com),  
[info@yshield.de](mailto:info@yshield.de)

**High quality primer supplied as concentrate, makes 5 liters of primer.** For priming of solid old coats of paint, brittle, chalky and absorbent substrates. Consolidating, adhesion promoting, good penetration, regulates the absorbency. Also recommended on our graphite shielding paints HSFxx, if **problematic (mineralic) coatings** should be applied.

### **Processing**

Mix the concentrate (1 liter) **with 4 liters of water. Gives 5 liters of primer.** If you use tap-water, process within 48 hours. For application use a first-class paint roller. Do not work at temperatures below 5°C/41°F. The consumption depends on the character and absorbency of the underground. Typical interior productivity 37.5 m², typical exterior productivity 25 m².

### **Ingredients**

Pure-acrylic binder, additives, preservative (BIT, INN, MIT).

### **TÜV-SÜD certification**

**We have our shielding paints monitored by TÜV-SÜD.** The whole production process including quality control, emission behaviour and economical use of preserving agents is subject to monitoring. **Please find the certificate above at the downloads.**