


## TENMARS TM-192 | Magnetic field meter

3-axis sensor (X/Y/Z), frequency range 30 Hz - 2000 Hz, display in mG or  $\mu\text{T}$ .



YSHIELD® TM-192



YSHIELD® TM-192 / Battery without shielding



YSHIELD® TM-192 / Battery with shielding

**Compact and easy-to-use measuring device for measuring alternating magnetic fields ELF.** Surprisingly accurate despite the low price compared to professional measuring technology from Narda, Gigahertz, Fauser, etc.

Perfect for quick and easy checking of **magnetic fields in your car, electric car, van, camper, caravan**, etc. Many other applications in buildings such as **power cables, fuse boxes, solar systems** (panels, inverters, cabling).

### Technical data

- **Frequency range:** 30 Hz to 2000 Hz
- **Measuring range:** 20 / 200 / 2000 mG or 2 / 20 / 200  $\mu\text{T}$
- **Resolution:** 0.01 / 0.1 / 1 mG or 0.001 / 0.01 / 0.1  $\mu\text{T}$  = 1 nT
- Data hold function (HOLD), maximum hold function (MAX), minimum hold function (MIN)
- Dimensions: 17.3 cm x 8.0 cm x 3.2 cm
- Warranty: 1 year
- Weight: 230 g
- Power supply: 9 V battery
- Scope of delivery: measuring device, carrying case, operating instructions in English

YSHIELD GmbH & Co. KG  
94099 Ruhstorf, Germany  
[www.yshield.com](http://www.yshield.com)  
[info@yshield.de](mailto:info@yshield.de)